


V90 MMT 3"



MATERIALS

- #1-2 HOSE & BRAID: STAINLESS STEEL HOSE WITH 1-LAYER OF STAINLESS STEEL BRAID
- #3 BRAID COLLAR: STAINLESS STEEL
- #4 END FITTING: SCH. 40 CARBON STEEL MALE NPT
- #5 ELBOWS: SCH. 40 CARBON STEEL



#6 PORT (OPTIONAL):

#7 HANGER (OPTIONAL):

QTY	MODEL NUMBER	SIZE	OAL DIM.	"H" DIM.	WRK. PSIG	MAX TEST	MOTION X,Y,Z	WT. LBS.
	SV050013	1/2"	25 1/2"	8 3/4"	796	1194	3"	2
	SV075013	3/4"	27"	10 1/4"	597	895	3"	3
	SV100013	1"	30 1/4"	11 1/4"	455	682	3"	5
	SV125013	1 1/4"	33 3/4"	12 3/4"	441	661	3"	7
	SV150013	1 1/2"	37"	14 1/4"	370	555	3"	9
	SV200013	2"	41 1/2"	16 1/4"	370	555	3"	15
	SV250013	2 1/2"	41 1/4"	15 3/4"	390	585	3"	25
	SV300013	3"	45"	17 1/4"	250	375	3"	30

TEMPERATURE DERATING FACTORS: MULTIPLY X WRK. PSIG									
200° F	250° F	300° F	350° F	400° F	500° F	600° F	700° F	800° F	900° F
0.94	0.92	0.88	0.86	0.83	0.78	0.74	0.7	0.66	0.62

DRAWN BY:

DRAWING NUMBER:

REV:

SIGNATURE:

DATE:

PO NUMBER:

PROJECT:

CUSTOMER:

NOTES: